




NTN BEARING CORP.

40,000 mm x 90,000 mm x 23,000 mm NTN
CS308LLU deep groove ball bearings



Bearing No. CS308LLU

CS308LLU Bearing 2D drawings and 3D CAD models

Size	40x90x23 mm
Bore Diameter	40,000 mm
Outer Diameter	90,000 mm
Width	23,000 mm
d	40,000 mm
D	90,000 mm
B	23,000 mm
C	23,000 mm
Category	Insert Bearings Spherical OD
Inventory	4.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.621
Product Group	M06110
Inner Race Profile	Standard Inner Ring
Outer Race Profile	Spherical
Relubricatable	No
Seal Type	Contact
Mounting Method	Shaft Mount
Rolling Element	Ball Bearing
Snap Ring	No
Long Description	40MM Bore; Standard Inner Ring; Ball Bearing; 23MM Length Thru Bore; 23MM Outer Race Width; 90MM Outside Diameter; Not



NTN BEARING CORP.

	Relubricatable; Contact Seal; Shaft Mount Mounting Method; No Snap Ring
Inch - Metric	Metric
Other Features	Single Row Heavy Duty Metric
Category	Insert Bearings
UNSPSC	31171536
Harmonized Tariff Code	8482.10.50.00
Noun	Bearing
Keyword String	Insert
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	CS308LLU
Weight / LBS	1.367
Length Thru Bore	0.906 Inch 23 Millimeter
Bore	1.575 Inch 40 Millimeter
Outer Race Width	0.906 Inch 23 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
bore diameter:	40 mm
static load capacity:	24000 N
outside diameter:	90 mm
precision rating:	Class 0
overall width:	23 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	Through Hardened Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	23 mm
snap ring included:	Without Snap Ring
outer ring width:	23 mm



NTN BEARING CORP.

internal clearance:	CN
fillet radius:	2 mm
operating temperature range:	-40 to 120 ° C
manufacturer product page:	Click here
dynamic load capacity:	40500 N